

OM3 Fiber Jumpers

Description:

FIBERONE® OM3 fiber jumpers come simplex or duplex housing 50/125um Corning® InfiniCor fibers. Each is made to standard or custom with various options. Our jumpers are available in either a standard riser-rated or a fire-retardant jacket, at any length, with a 2.0mm or 3.0mm PVC jacket. FIBERONE offers a pre-terminating service based on your choice of SC, LC, FC and ST connectors. FIBERONE addresses quality assurance through their individual hand testing process and service guarantee.



Features:

- Simplex or Duplex
- Standard or Custom Lengths
- Various Connector & PVC Jacket Options
- PC Polish
- Riser Rated or Plenum
- 100% Tested & Guaranteed

Specifications:

| Connector Types | SC | LC | FC | ST |
|-------------------------|--|-----------|-----------|-----------|
| Insertion Loss (dB) | Max. 0.40 | Max. 0.40 | Max. 0.40 | Max. 0.40 |
| Reflectance – PC Polish | -25 dB | -25 dB | -25 dB | -25 dB |
| Fiber / Cable Type | Corning® InfiniCor Multimode Fiber / Riser or Plenum | | | |
| PVC Jacket Thickness | 1.6, 2, or 3 mm Diameter | | | |
| Operating Temperature | -20 to 60 °C | | | |
| Color | Aqua | | | |
| Core Size | 50 um | | | |
| Data Rate | 10 GB @ 850 um | | | |
| Distance | Up to 300 meters | | | |
| Applications | High Speed Networks | | | |