

OM4 Fiber Jumpers

Description:

FIBERONE® OM4 fiber jumpers come simplex or duplex housing 50/125um Corning® InfiniCor fibers. Each is made to standard or custom with various options. Our jumpers are available in either a standard riser-rated or a fire-retardant jacket, at any length, with a 2.0mm or 3.0mm PVC jacket. FIBERONE offers a pre-terminating service based on your choice of SC, LC, FC and ST connectors. FIBERONE addresses quality assurance through their individual hand testing process and service guarantee.



Features:

- Simplex or Duplex
- Standard or Custom Lengths
- Various Connector & PVC Jacket Options
- PC Polish
- Riser Rated or Plenum
- 100% Hand Tested & Guaranteed

Specifications:

Connector Types	SC	LC	FC	ST
Insertion Loss (dB)	Max. 0.40	Max. 0.40	Max. 0.40	Max. 0.40
Reflectance – PC Polish	-25 dB	-25 dB	-25 dB	-25 dB
Fiber / Cable Type	Corning® InfiniCor Multimode Fiber / Riser or Plenum			
PVC Jacket Thickness	1.6, 2, or 3 mm Diameter			
Operating Temperature	-20 to 60 °C			
Temperature Color	Aqua			
Core Size	50 um			
Data Rate	10 GB @ 850 um			
Distance	Up to 550 meters			
Applications	High-Speed Networks – Data Centers, Financial Centers, & Corporate Campuses			